

MIN. 6" 19MM LAYER OF SUPER
PAVE HOT MIX BASE COURSE,
2-3" LIFTS (1½" TO BE MILLED
WITH PERMANENT LANE OVERLAY)

SAW CUT WITH APPROVED SAW
TO FULL PAVEMENT DEPTH.
(TYPICAL)

EXISTING SURFACE
COURSE

EXISTING BASE
COURSE

1'-0" MINIMUM
(TYPICAL)

WIDTH OF SURFACE COURSE 5' MIN.
4' MINIMUM FOR EDGE OF
ROAD REPAIRS ONLY.

NOTE:

IF PATCH FALLS WITHIN 2' OF
EXISTING CURB OR EDGE OF
PAVING, CONTINUE RESTORATION
TO CURB.

DENSE GRADED AGGREGATE BASE
COURSE, 9" MINIMUM THICKNESS.

BACKFILL IN ACCORDANCE WITH
APPLICABLE TRENCH DETAIL

PERMANENT CROSS ROAD AND LONGITUDINAL TRENCH REPAIR

(HOT MIX OVER CRUSHER RUN TYPE BASE COURSE.)

NOTE:

1. PATCH PAVING SECTION SHALL BE AS NOTED OR EXCEED EXISTING PAVEMENT THICKNESSES
2. PATCH PAVING SECTION SHOWN HEREIN SHALL BE INCREASED AS APPLICABLE TO PROVIDE STRUCTURAL NUMBER REQUIRED BY TRAFFIC VOLUME.

APPROVAL

[Signature]
TOWN ENGINEER

7/20/09
DATE

REVISED

TOWN OF EASTON
AND
EASTON UTILITIES
STANDARD DETAILS

PAVEMENT RESTORATION DETAIL #1

ISSUED: FEB 25, 2009

STANDARD NO. PW-1.06